



600 Kw Cummins 3 Phase Diesel Generator 50HZ 60HZ With Water Cooling System

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: DELLENT-Cummins
- Certification: CE/ISO9001
- Model Number: DE-CC825
- Minimum Order Quantity: 1 PC
- Price: bargain face-to-face
- Packaging Details: PLASTIC WRAP OR PLYWOOD CASE
- Delivery Time: 20-30 DAYS
- Payment Terms: L/C, T/T
- Supply Ability: 1 MONTH 600PCS



Product Specification

- Name: Cummins 3 Phase Diesel Generator
- Engine Brand: Cummins
- Cooling Method: Water-Cooling System
- Fuel Type: Diesel
- Rated Frequency: 50HZ/60HZ
- Speed: 1500RPM/1800RPM
- Warranty: 12 Months/1000 Hours
- Highlight: **Cummins 3 Phase Diesel Generator 50HZ,
CE Cummins 3 Phase Diesel Generator,
600 Kw Cummins Generator**

for more products please visit us on dellentpower.com

CE Cummins Diesel Generator about 600kW.

As an authorized Cummins generator dealer, we offer a wide range of models to suit any power needs and budget. From compact and portable generators to heavy-duty industrial generators, we have the expertise and resources to help you find the perfect generator for your needs.

At our Cummins generator dealership, we understand the importance of quality and reliability when it comes to power generation. That's why we only offer the best generators from Cummins , a leading manufacturer of power equipment.

. PRODUCT

50-0225 TECHNICAL DATA

General Information		Engine Performance		Generator Performance		Efficiency (%)		Speed (rpm)		Frequency (Hz)		Voltage (V)		Phase	
Model	Power (kW)	Power (kVA)	Engine (kW)	Engine (kVA)	Generator (kW)	Generator (kVA)	Efficiency (%)	Speed (rpm)	Frequency (Hz)	Voltage (V)	Phase	Voltage (V)	Phase	Voltage (V)	Phase
50-0225	25	33.3	25	33.3	25	33.3	95	1800	50	400	3	400	3	400	3
50-0230	30	39.6	30	39.6	30	39.6	95	1800	50	400	3	400	3	400	3
50-0235	35	45.9	35	45.9	35	45.9	95	1800	50	400	3	400	3	400	3
50-0240	40	52.2	40	52.2	40	52.2	95	1800	50	400	3	400	3	400	3
50-0245	45	58.5	45	58.5	45	58.5	95	1800	50	400	3	400	3	400	3
50-0250	50	64.8	50	64.8	50	64.8	95	1800	50	400	3	400	3	400	3
50-0255	55	71.1	55	71.1	55	71.1	95	1800	50	400	3	400	3	400	3
50-0260	60	77.4	60	77.4	60	77.4	95	1800	50	400	3	400	3	400	3
50-0265	65	83.7	65	83.7	65	83.7	95	1800	50	400	3	400	3	400	3
50-0270	70	90.0	70	90.0	70	90.0	95	1800	50	400	3	400	3	400	3
50-0275	75	96.3	75	96.3	75	96.3	95	1800	50	400	3	400	3	400	3
50-0280	80	102.6	80	102.6	80	102.6	95	1800	50	400	3	400	3	400	3
50-0285	85	108.9	85	108.9	85	108.9	95	1800	50	400	3	400	3	400	3
50-0290	90	115.2	90	115.2	90	115.2	95	1800	50	400	3	400	3	400	3
50-0295	95	121.5	95	121.5	95	121.5	95	1800	50	400	3	400	3	400	3
50-0300	100	127.8	100	127.8	100	127.8	95	1800	50	400	3	400	3	400	3
50-0305	105	134.1	105	134.1	105	134.1	95	1800	50	400	3	400	3	400	3
50-0310	110	140.4	110	140.4	110	140.4	95	1800	50	400	3	400	3	400	3
50-0315	115	146.7	115	146.7	115	146.7	95	1800	50	400	3	400	3	400	3
50-0320	120	153.0	120	153.0	120	153.0	95	1800	50	400	3	400	3	400	3
50-0325	125	159.3	125	159.3	125	159.3	95	1800	50	400	3	400	3	400	3
50-0330	130	165.6	130	165.6	130	165.6	95	1800	50	400	3	400	3	400	3
50-0335	135	171.9	135	171.9	135	171.9	95	1800	50	400	3	400	3	400	3
50-0340	140	178.2	140	178.2	140	178.2	95	1800	50	400	3	400	3	400	3
50-0345	145	184.5	145	184.5	145	184.5	95	1800	50	400	3	400	3	400	3
50-0350	150	190.8	150	190.8	150	190.8	95	1800	50	400	3	400	3	400	3
50-0355	155	197.1	155	197.1	155	197.1	95	1800	50	400	3	400	3	400	3
50-0360	160	203.4	160	203.4	160	203.4	95	1800	50	400	3	400	3	400	3
50-0365	165	209.7	165	209.7	165	209.7	95	1800	50	400	3	400	3	400	3
50-0370	170	216.0	170	216.0	170	216.0	95	1800	50	400	3	400	3	400	3
50-0375	175	222.3	175	222.3	175	222.3	95	1800	50	400	3	400	3	400	3
50-0380	180	228.6	180	228.6	180	228.6	95	1800	50	400	3	400	3	400	3
50-0385	185	234.9	185	234.9	185	234.9	95	1800	50	400	3	400	3	400	3
50-0390	190	241.2	190	241.2	190	241.2	95	1800	50	400	3	400	3	400	3
50-0395	195	247.5	195	247.5	195	247.5	95	1800	50	400	3	400	3	400	3
50-0400	200	253.8	200	253.8	200	253.8	95	1800	50	400	3	400	3	400	3
50-0405	205	260.1	205	260.1	205	260.1	95	1800	50	400	3	400	3	400	3
50-0410	210	266.4	210	266.4	210	266.4	95	1800	50	400	3	400	3	400	3
50-0415	215	272.7	215	272.7	215	272.7	95	1800	50	400	3	400	3	400	3
50-0420	220	279.0	220	279.0	220	279.0	95	1800	50	400	3	400	3	400	3
50-0425	225	285.3	225	285.3	225	285.3	95	1800	50	400	3	400	3	400	3
50-0430	230	291.6	230	291.6	230	291.6	95	1800	50	400	3	400	3	400	3
50-0435	235	297.9	235	297.9	235	297.9	95	1800	50	400	3	400	3	400	3
50-0440	240	304.2	240	304.2	240	304.2	95	1800	50	400	3	400	3	400	3
50-0445	245	310.5	245	310.5	245	310.5	95	1800	50	400	3	400	3	400	3
50-0450	250	316.8	250	316.8	250	316.8	95	1800	50	400	3	400	3	400	3
50-0455	255	323.1	255	323.1	255	323.1	95	1800	50	400	3	400	3	400	3
50-0460	260	329.4	260	329.4	260	329.4	95	1800	50	400	3	400	3	400	3
50-0465	265	335.7	265	335.7	265	335.7	95	1800	50	400	3	400	3	400	3
50-0470	270	342.0	270	342.0	270	342.0	95	1800	50	400	3	400	3	400	3
50-0475	275	348.3	275	348.3	275	348.3	95	1800	50	400	3	400	3	400	3
50-0480	280	354.6	280	354.6	280	354.6	95	1800	50	400	3	400	3	400	3
50-0485	285	360.9	285	360.9	285	360.9	95	1800	50	400	3	400	3	400	3
50-0490	290	367.2	290	367.2	290	367.2	95	1800	50	400	3	400	3	400	3
50-0495	295	373.5	295	373.5	295	373.5	95	1800	50	400	3	400	3	400	3
50-0500	300	379.8	300	379.8	300	379.8	95	1800	50	400	3	400	3	400	3
50-0505	305	386.1	305	386.1	305	386.1	95	1800	50	400	3	400	3	400	3
50-0510	310	392.4	310	392.4	310	392.4	95	1800	50	400	3	400	3	400	3
50-0515	315	398.7	315	398.7	315	398.7	95	1800	50	400	3	400	3	400	3
50-0520	320	405.0	320	405.0	320	405.0	95	1800	50	400	3	400	3	400	3
50-0525	325	411.3	325	411.3	325	411.3	95	1800	50	400	3	400	3	400	3
50-0530	330	417.6	330	417.6	330	417.6	95	1800	50	400	3	400	3	400	3
50-0535	335	423.9	335	423.9	335	423.9	95	1800	50	400	3	400	3	400	3
50-0540	340	430.2	340	430.2	340	430.2	95	1800	50	400	3	400	3	400	3
50-0545	345	436.5	345	436.5	345	436.5	95	1800	50	400	3	400	3	400	3
50-0550	350	442.8	350	442.8	350	442.8	95	1800	50	400	3	400	3	400	3
50-0555	355	449.1	355	449.1	355	449.1	95	1800	50	400	3	400	3	400	3
50-0560	360	455.4	360	455.4	360	455.4	95	1800	50	400	3	400	3	400	3
50-0565	365	461.7	365	461.7	365	461.7	95	1800	50	400	3	400	3	400	3
50-0570	370	468.0	370	468.0	370	468.0	95	1800	50	400	3	400	3	400	3
50-0575	375	474.3	375	474.3	375	474.3	95	1800	50	400	3	400	3	400	3
50-0580	380	480.6	380	480.6	380	480.6	95	1800	50	400	3	400	3	400	3
50-0585	385	486.9	385	486.9	385	486.9	95	1800	50	400	3	400	3	400	3
50-0590	390	493.2	390	493.2	390	493.2	95	1800	50	400	3	400	3	400	3
50-0595	395	499.5	395	499.5	395	499.5	95	1800	50	400	3	400	3	400	3
50-0600	400	505.8	400	505.8	400	505.8	95	1800	50	400	3	400	3	400	3
50-0605	405	512.1	405	512.1	405	512.1	95	1800	50	400	3	400	3	400	3
50-0610	410	518.4	410	518.4	410	518.4	95	1800	50	400	3	400	3	400	3
50-0615	415	524.7	415	524.7	415	524.7	95	1800	50	400	3	400	3	400	3
50-0620	420	531.0	420	531.0	420	531.0	95	1800	50	400	3	400	3	400	3
50-0625	425	537.3	425	537.3	425	537.3	95	1800	50	400	3	400	3	400	3
50-0630	430	543.6	430	543.6	430	543.6	95	1800	50	400	3	400	3	400	3
50-0635	435	549.9	435	549.9	435	549.9	95	1800	50	400	3	400	3	400	3
50-0640	440	556.2	440	556.2	440	556.2	95	1800	50	400	3	400	3	400	3
50-0645	445	562.5	445	562.5	445	562.5	95	1800	50	400	3	400			



. FACTORY INTERIOR:



Fuan Dellent Electric & Machinery Co., Ltd.



+8613706938606



jennifer@dellent.com



dellentpower.com

NO.7,JINYE ROADTIEHU INDUSTRIAL AREA CHENGYANG TOWN, FUAN
CITY,NINGDE CITY,FUJIAN.CHINA